



WBS 1.4 Optical (Laser) Calibration

John A.J. Matthews

johnm@phys.unm.edu




University of New Mexico

Albuquerque, NM 87131

FOR

HAWC Calibration Team at: Colorado State U. (CSU), George Mason U.,
LANL, Michigan Technological U. (MTU) and U. of New Mexico (UNM)

HAWC challenges ...




- (Top Left) Shower front timing residuals vs distance from shower core; (Top Right) Timing residuals (nsec) near the shower *core*.
- Precision angular reconstruction then needs the PMT timing offsets (errors) to be $< 1\text{ ns}$.
- DAQ emphasis on precision timing (Bottom Left) results in the signal amplitude being *coded* as **T**ime **o**ver **T**hreshold (**ToT**).

HAWC calibration *design* ...




Fiber Layouts




- Use a pulsed (300ps, 532nm laser) light source of **known** intensity and with **known** light transit time to the PMTs.
- Adjust the source intensity (using neutral density filters) over the (required) PMT dynamic range of $\sim 0.1\text{PE}$ to $\sim 10^4\text{PEs}$.
- Repeat 300 times (for 300 WCDs). **Begin with the HAWC WCD prototype at CSU**

HAWC calibration *calibration at CSU WCD ...*




- The prototype HAWC WCD at CSU has allowed R&D on all components (hardware, control software and analysis) of the calibration system.
- Major group calibration responsibilities include:
 1. CSU: calibration data analysis, muon calibration
 2. George Mason U: muon calibration
 3. LANL: DAQ for TDCs
 4. MTU: calibration control software and data analysis
 5. UNM: calibration hardware, control software and data analysis





HAWC calibration schematic ...




- The *ingredients* for a calibration include: the light-to-WCD Intensity (**Radiometer 2**), and digitization of the laser pulse time (T_{start}) and the PMT (**time** and **ToT**).

HAWC calibration *cycle* ...



Occupancy Measurements





- A calibration **cycle** involves ~ 2000 light pulses/intensity at 150 discrete intensities.
- The PMT **occupancy** (*i.e.* fraction of laser pulses with PMT signal $> V_{Lo}$) is related to the average number of PEs, $\langle n_{PE} \rangle$, at that intensity (**RM2 energy (J)**).
- This is merged with the distribution of **ToT** (at that **RM2 energy (J)**) to obtain:
ToT $\rightarrow n_{PE}$ for each of the PMTs (5 in this data from CSU) in the WCD.



HAWC calibration “Maximum PEs” at CSU ...



Maximum Intensities in PE



- The CSU prototype HAWC WCD has been in routine data taking for calibration R&D since spring 2011.
- This tank includes 5 (4 plus one with reflective baffle) PMTs and 4 selectable calibration light diffusers.
- Maximum PMT calibration signals (PEs), temporarily reduced by $\sim 4\times$, meet the design goal of $\sim 10,000$ PEs (dotted line in plot).





HAWC calibration *stability at CSU* ...



- (Left plots): Variation in the **Maximum PE** values for different analysis *fit ranges* and for two different PMTs vs calibration cycle.
- (Top plots): Variation in the **1PE→ToT** values for all 5 PMTs vs calibration cycle.
- Both **Maximum PE** and **1PE** calibration results show variations of $1 \sim 2\%$.

HAWC calibration deliverables (from CSU) (I) ...




- (Top Left) Relation between what HAWC measures: PMT **ToT** and the PMT signal in PEs. The PMT signal in PEs is needed for shower plane reconstruction and γ -hadron separation.
- (Top Right) Time slewing correction (nsec) vs the measured PMT signal in **ToT**. The slewing correction is needed for shower plane reconstruction.
- Note: Time slewing \equiv time between laser and PMT pulses; **ToT**(ns) = **ToT**/10.24.

HAWC calibration deliverables (from CSU) (II) ...



Channel 4




- A first look at the **stability** of (one) PMT's **slewing correction** is encouraging ...




HAWC calibration *final control software* ...

CalDaemon States



Class Hierarchy




- The HAWC calibration control software, developed at MTU, is now mature.
- The MTU HAWC software (and control computer) will move to CSU soon.
- Development of the *calibration and experiment control software*, optimization of the calibration parameters, debugging problems from the HAWC site, and extensive calibration studies will continue at CSU for the foreseeable future.

HAWC calibration *status/plans (I)* ...




- Calibration studies have benefited from essentially complete *HAWC calibration systems* at CSU and MTU. A small subset of the studies are reported in this talk.
- What has been demonstrated includes:
 1. the successful, automated (continuous), remote operation of the calibration and DAQ at CSU:
 - the light pulses span the PMT dynamic range of $0.1 \sim 10^4$ PEs
 - the monitoring of light pulse intensities (over the full dynamic range)
 2. calibration-to-calibration differences of calibration constants show only small variations (at the few percent level)
- What is still in progress includes:
 1. automated, remote operation of the *round-trip-timing* monitoring of the light delivery times to the WCDs
 2. checks on the stability and possible systematic variations in the time slewing corrections VS signal **ToT**
 3. automated, remote operation of the (final) calibration control software

HAWC calibration *status/plans* (II) ...



- For HAWC30 we need additional parts:
 1. Overall *upgrade* from 1-tank to 30⁺-tank instrumentation
 2. Implement *minor* design changes based on CSU/MTU studies
 3. Address remaining issues ... *e.g. excess fiber storage*
- Complete upgrade of MTU hardware; then ship to Mexico
- Highest priority: ordering and shipping ...

HAWC calibration *summary* ...



- The HAWC (laser) calibration system, and the analysis of the calibration data, are both well advanced.
- HAWC muon calibration (not presented): scintillator paddles are being procured and studies have begun of the response of the HAWC CSU WCD to muons.
- Current focus for HAWC30: ordering and shipping.
- Projected aggregate costs for the (laser) calibration (excluding shipping, customs and installation) are consistent with a \$265K budget.

Additional/backup slides



Additional slides